

SmallRig



Cage (for Panasonic G9 II / S5 II / S5 IIX)

Operating Instruction

SmallRig Cage for Panasonic LUMIX G9 II / S5 II / S5 IIX 4022 is designed to attach accessories and protect the camera. It locks the camera via one bottom 1/4"-20 screw and two side lock adapters, with rubber pads preventing scratches. Among its accessory mounting points, 1/4"-20 holes and ARRI 3/8"-16 locating holes support Top Handle 2165C, Side Handle 2093, etc. for easy camera movement and more stability; the front 1/4"-20 locating hole suits Rod Clamp 3276 for follow focus system; and the top ARRI 3/8"-16 locating hole fits Monitor Mount 2903B. It also comes with two cold shoe mounts to attach microphone, LED video light; a top NATO rail for Top Handle 3322; a left NATO rail for Side Handle 3847; and a bottom QD socket to install QD shoulder strap. At the bottom there is an Arca-Swiss quick-release plate, suitable for DJI RS 2 / RSC 2 / RS 3 / RS 3 Pro gimbals and Arca-Swiss tripods, as well as a threaded hole for DJI RS 2 / RSC 2 gimbal quick-release plate (height increase pad) and Arca-Swiss Quick Release Plate 3154. The item also features strap holes on both sides and the bottom, which are compatible with Hand Strap PAC2456, Shoulder Strap PSC2428, etc. Besides, a magnetic wrench is included for easy disassembly and assembly.

Safety Guidelines

1. Environment

Do not use the product underwater, in extreme temperatures (e.g., freezing or direct heat), corrosive environments, or excessive dust. Dry metal parts immediately after liquid contact to prevent corrosion.

2. Load Capacity

Do not exceed the maximum weight capacity indicated on the product. Overloading risks structural failure, deformation, or accidental drops.

3. Cleaning & Maintenance

Clean surfaces with a dry, soft cloth. Avoid chemicals like alcohol or solvents. Ensure dry and ventilated conditions for long-term storage.

4. Structural Integrity

Do not modify the product (e.g., drilling, cutting)—this compromises structural integrity and increases drop risks.

5. Malfunctions

Stop use immediately if you notice deformation, unusual noises, or loose components, and contact support.




In the Box

Guarantee Card × 1

Mini V Mount Battery Plate × 1

Allen Wrench × 1

Product Details



How to use

STEP①: Remove the side lock adapters




STEP②: Slide the camera into cage



STEP③: Locking bottom 1/4"-20 screw



STEP④: Locking the right side lock adapter



STEP⑤: Locking the left side lock adapter

Specifications



Product Dimensions: 147.5 × 62 × 118.5mm

Package Dimensions: 180 × 129.5 × 75mm

Product Weight: 161g ± 5g

Package Weight: 242g ± 5.0g

Material(s): Aluminum Alloy, Stainless Steel

Manufacturer Email: support@smallrig.com

Manufacturer: Shenzhen Leqi Innovation Co., Ltd.

Add: Rooms 101, 701, 901, Building 4, Gonglianfuji Innovation Park, No. 58, Ping'an Road,
Dafu Community, Guanlan Street, Longhua District, Shenzhen, Guangdong, China.

Consignor: Shenzhen LC Co., Ltd.

Add: Room 201, Building 4, Gonglianfuji Innovation Park, No. 58, Ping'an Road,
Dafu Community, Guanlan Street, Longhua District, Shenzhen, Guangdong, China.

RoHS

CE



FR
LE TRI
+ FACILE



+
Papier 5



Séparez les éléments avant de trier



Made in China